

Bez.: MCX-Stecker, 50 Ohm, Crimpausführung, Teflon-Isolation, für RG 178/196/U

Technical drawing of a cable assembly. The drawing includes a side view, a cross-section view, and a detail view of the crimp. Dimensions are provided in millimeters.

Dimensions:

- Overall length: 12.7 ± 0.4
- Length of the crimped section: 5 ± 0.4
- Length of the straight section: 3.4
- Outer diameter of the crimped section: $\phi 5$
- Inner diameter of the crimped section: $\phi 3$
- Inner diameter of the crimped section (crimp size): $\phi 2.3$
- Length of the straight section (from crimp to tip): 7.4
- Tip diameter: $\phi 1.9$
- Tip length: 0.6
- Tip diameter (detail): $\phi 1.7$
- Tip length (detail): 0.7
- Tip diameter (detail): $\phi 1.9$
- Tip length (detail): 5.3

Table:

CABLE	A	B	C	D

CABLE	A	B	C	D
RG178	ø0.5	ø1.0	ø1.45	ø1.9

$$1000-2000=\pm 2.4$$

06	FERRULE 	BRASS	1	GOLD
05	INSULATOR GASKET	TEFLON	1	
04	CENTER PIN	BRASS	1	GOLD
03	CABLE BODY	BRASS	1	GOLD
02	INSULATOR	TEFLON	1	
01	BODY	BERYLLIUM COPPER	1	GOLD
NO	DESCRIPTION	MATERIAL	Q'TY	FINISH

TITLE: MCX CRIMP PLUG FOR RG178/U CABLE